



GBREP

جي بي رب

Polymer Modified, Fiber Reinforced, High Strength cement-based, Repair Mortar

Added Value

- The mix and application is very easy with **GBRep** since it is a sticky material
- The application is up to 10 cm is easy in 2-3 layers.

Economic and Easy to Apply

- Economic since one bag (25 Kg.) of **GBRep** is sufficient for 2-3 meters in a thickness of 5 mm.

Product Specifications

- Gray powder with aggregate size up to 3mm.
- Mixed Density: 2 kg/L.
- Application time : 45 Min.
- Compressive Strength: >40 N/ mm².
- Adhesion Strength : 1.5 N/ mm².
- Flexural Strength: > 7 N/ mm².
- Water Absorption (%): < 2.5
- Mixing Water : 4-5 Liters / Pack 25 Kg.
- Water permeability@ 5 bar pressure: <10 mm.
- Valid for 1 year in an unopened packs.



GBRep, Product Features

- ❖ **GBRep** is a polymer modified, fibre reinforced repair mortar specially designed for concrete and cementitious surfaces, to repair and level the surfaces with high thickness, and high strength mortar.
- ❖ **GBRep** is treated with special aggregates to be similar to concrete and improve the ability to build repair areas and patching concrete with high build thickness up to 10 cm (with layers).
- ❖ It is also treated with natural fiber to prevent any cracking of the repaired surface.
- ❖ **GBRep** is a sticky material which enhances the adhesion of the mortar to concrete and cementitious surfaces without de-bonding after aging.



Application Fields

- Repair of concrete floors, for Factories, Commercial areas, and Storage areas.
- Leveling of swimming pools walls before application of waterproofing layers..
- Repair precast units for fences, gardens, and concrete planting units.
- Repair of concrete columns and ceilings.

Health and Safety

- Wear gloves and goggles while application.
- The material is not harmful for skin.
- Water-based, washing out with plenty of water.

Packing

- A plastic double bag contains 25 kg. of **GBRep**.

Improvements:

- ❖ The application of **GBRep** ensures good adhesion to concrete and cement based surfaces.
- ❖ **GBRep** prevents the formation of surface cracks.
- ❖ **GBRep** improves the repair thickness up to to 10 cm without any de-bonding with aging.

Application Procedure

- ❖ One pack of **GBRep** is mixed with 4-5 litres of clean water and mixed well till homogeneity.
- ❖ A rush coat of the same material may be applied in case of smooth surfaces.
- ❖ Apply by traditional and manual way in layers the max layer thickness is 3 cm.
- ❖ After final application the surface should be cured with water for at least 2 days.



**Green Build
Egypt**
Experience and Innovation

www.greenbuildegypt.com
info@greenbuildegypt.com
<https://www.facebook.com/GreenBuildEgypt>

Customer Service: 01050240446/ 01114544492
LandLine: 02-28607233
51 First Industrial Area Badr City, Cairo, Egypt.

